

quietCure™
by floorMuffler®

it's what's underneath that counts®



QuietCure™ is an Acoustic Underlayment & Moisture Barrier for use in residential and commercial flooring applications. As part of our *Professional Collection*, QuietCure is an excellent choice for most Laminate, Engineered and Solid hardwood flooring installations. QuietCure can be used in Floating, Nail down, and Double glue down installations. Available both with and without UltraSeal self-sealing lip & tape system.

TYPICAL PHYSICAL PROPERTIES SHEET





QuietCure™ is an Acoustic Underlayment & Moisture Barrier for use in residential and commercial flooring applications. As part of our *Professional* Collection, QuietCure is an excellent choice for most Laminate, Engineered and Solid hardwood flooring installations. QuietCure can be used in Floating, Nail down, and Double glue down installations. Available both with and without UltraSeal self-sealing lip & tape system.

TYPICAL PHYSICAL PROPERTIES SHEET

GENERAL PROPERTIES

Item Name	QuietCure™ / QuietCure™ UltraSeal
Construction	Closed cell, polypropylene foam
Overlap Options	Available with & w/o UltraSeal Self Sealing Lip & Tape
Thickness	2 mm
Coverage Area	100 sf
Standard Roll Size	39" wide x 30.75 lf
Product Grade	Professional

PERFORMANCE

Impact Isolation Class (IIC)	up to (71) dB per ASTM E 492 / ASTM E 989
Delta Impact Isolation Class (ΔIIC)	up to (25) dB per ASTM E 2179
Sound Transmission Class (STC)	up to (66) dB per ASTM E 90
Moisture Vapor Transmission Rate	(1.5) lbs / 1000 ft ² / 24 hr. per ASTM E 96
Compressive Strength @ 25%	≥ 7.3 psi per ASTM D 3575
Warranty Period	25 Years
Mold and Mildew Resistant	Yes
R Value	3 ft ² -F-hr/BTU-in
Volatile Organic Compounds (VOCs)	Surpasses California Section 03150
Recyclable	Yes

PACKAGING

Rolls / Carton	12
Cartons / Skid	10
Skids / TL	26
Rolls / TL	3,120
SF / Carton	1,200 sf
SF / Skid	12,000 sf
SF / TL	312,000 sf

The data represented on this Typical Property Sheet reflects averages derived from product sample testing on limited production runs, and may be changed without notice. Actual product properties are subject to normal manufacturing and testing tolerances. This is especially true for conventional measurements of weight, thickness, and density. This Typical Property Sheet is not intended to represent, replace, or be used as a proxy for a specific product sales specification. Please refer to our website at www.floormuffler.com for the most up to date product information, data, and installation instructions.



Diversified Industries
121 High Hill Road
Swedesboro, NJ 08085
is a proud member of the
MADE IN NEW JERSEY
Program

Let's Get Social



Professional
GRADE