



COMBOFOAM®

Combofoam® is a value grade flooring underlayment and moisture barrier. Available with self sealing lip and tape system.

USES

Laminate, Engineered and Solid hardwood flooring installations.

METHODS

Floating, Nail Down Installations.

APPLICATIONS



Residential



Commercial

MATERIAL

Polyethylene Foam

THICKNESS

2 mm


PRODUCT SPECS

SPECS	STANDARD SIZE
Coverage area	100 sf
Width	46 in
Length	26.09 ft
Diameter	5.5 in
Weight	2 lb
Rolls/Carton	18
Carton/Skid	8



ACOUSTIC PERFORMANCE


61 IIC
54 STC



MOISTURE PROTECTION

MVTR:

2 LBS
1000FT² - 24HRS.



THERMAL PERFORMANCE

R Value per inch:

2.5 FT²-F-HR/
BTU



COMPRESSIVE STRENGTH @25%

≥ 2.8 psi



ENVIROMENTAL

VOCs:

**Complies with
CA 1350**

The data represented on this Typical Property Sheet reflects averages derived from product sample testing on limited production runs, and may be changed without notice. Actual product properties are subject to normal manufacturing and testing tolerances. This is especially true for conventional measurements of *weight, thickness, and density*. This Typical Property Sheet is not intended to represent, replace, or be used as a proxy for a specific product sales specification. Please refer to our website at www.floormuffler.com for the most up to date product information, data, and installation instructions.

Let's get social



floormuffler.com
1 800 440 6008

