

FLOOR MUFFLER® ULTRASEAL

floorMuffler® is a high performance **Acoustic Underlayment & Moisture Barrier**. Available both with and without UltraSeal self-sealing lip & tape system.

USES

Laminate, Engineered and Solid hardwood and Rigid Core flooring* installations.

METHODS

Floating, Nail down, and Double glue down installations.

APPLICATIONS



MATERIAL

Cross Linked, Closed Cell Polypropylene Foam (XLPP)


THICKNESS

2 mm

PRODUCT SPECS


SPECS	STANDARD SIZE		CONTRACTOR SIZE	
Coverage area	100 sf	600 sf	1800 sf	3600 sf
Width	48 in	48 in	48 in	48 in
Length	25 ft	150 ft	450 ft	900 ft
Diameter	6 in	14 in	25 in	34 in
Weight	2 lb	12 lb	33 lb	67 lb

* 5mm or thicker



ACOUSTIC PERFORMANCE


74 IIC **73** STC
76 HIIC **25** ΔIIC



MOISTURE PROTECTION

MVTR:


0.3 LBS
1000FT² - 24HRS.



THERMAL PERFORMANCE


R Value per inch:

4.3 FT²-F-HR/
BTU




COMPRESSIVE STRENGTH @25%

≥ 11 psi



FLAMMABILITY

CLASS A



ENVIROMENTAL

Mold & Mildew resistant:

YES

VOCs:

**Compliant with
CA 01350**

The data represented on this Typical Property Sheet reflects averages derived from product sample testing on limited production runs, and may be changed without notice. Actual product properties are subject to normal manufacturing and testing tolerances. This is especially true for conventional measurements of weight, thickness, and density. This Typical Property Sheet is not intended to represent, replace, or be used as a proxy for a specific product sales specification. Please refer to our website at www.floormuffler.com for the most up to date product information, data, and installation instructions.

Let's get social



floormuffler.com
1 800 440 6008

