



FLOORMUFFLER® LVT ENCORE

floorMuffler® LVT Encore is a high performance Acoustic Underlayment & Moisture Barrier for use in residential and commercial flooring applications.

PRODUCT SPECS

| SPECS | STANDARD SIZE | CONTRACTOR SIZE |
|---------------|---------------|-----------------|
| Coverage area | 100 sf | 600 sf |
| Width | 39 in | 72 in |
| Length | 30.75 ft | 100 ft |
| Diameter | 5.5 in | 8.5 in |
| Weight | 2 lb | 13 lb |
| Rolls/Carton | 20 | 15 |
| Carton/Skid | 10 | 2 |

USES

Luxury Vinyl and Rigid Core flooring with pre-attached pad.

METHODS

Floating Installations.

APPLICATIONS



MATERIAL

Cross Linked, Closed Cell Polypropylene Foam (XLPP)


THICKNESS

1.1 mm



ACOUSTIC PERFORMANCE

69 IIC
62 STC
22 ΔIIC



MOISTURE PROTECTION

MVTR:

0.2 LBS
1000FT² - 24HRS.



THERMAL PERFORMANCE

R-Value per inch:

4.1 FT²-F-HR/
BTU



COMPRESSIVE STRENGTH @25%

≥ 40 psi



FLAMMABILITY

CLASS A



ENVIRONMENTAL

Mold & Mildew resistant:

YES

VOCs:

**Compliant with
CA 01350**

The data represented on this Typical Property Sheet reflects averages derived from product sample testing on limited production runs, and may be changed without notice. Actual product properties are subject to normal manufacturing and testing tolerances. This is especially true for conventional measurements of weight, thickness, and density. This Typical Property Sheet is not intended to represent, replace, or be used as a proxy for a specific product sales specification. Please refer to our website at www.floormuffler.com for the most up to date product information, data, and installation instructions.

Let's get social



floormuffler.com

1 800 440 6008

