

FLOORMUFFLER® ENCORE

FloorMuffler® encore is a high performance Acoustic Underlayment & Moisture Barrier for use in residential and commercial flooring applications.

PRODUCT SPECS

SPECS	DIY SIZE	STANDARD SIZE	CONTRACTOR SIZE
Coverage area	100 sf	100 sf	600 sf
Width	48 in	39 in	72 in
Length	25 ft	30.75 ft	100 ft
Diameter	4.75 in	5.5 in	8.5 in
Weight	2 lb	2 lb	13 lb
Rolls/Carton	n/a	20	15
Carton/Skid	n/a	10	2

USES

Vinyl plank and rigid core flooring coverings with or without a pre-attached pad

METHODS

Floating Installations.

APPLICATIONS



Residential




Commercial

MATERIAL

Cross Linked, Closed Cell Polypropylene Foam (XLPP)


THICKNESS

1.1 mm




ACOUSTIC PERFORMANCE

69 IIC **62** STC
76 HIIC **22** ΔIIC




MOISTURE PROTECTION

MVTR:
0.2 LBS
 1000FT² - 24HRS.



THERMAL PERFORMANCE

R Value per inch:
4.1 FT²-F-HR/
 BTU




COMPRESSIVE STRENGTH @25%

≥ 40 psi



FLAMMABILITY

CLASS A



ENVIROMENTAL

Mold & Mildew resistant:
YES
 VOCs:
Compliant with CA 01350

The data represented on this Typical Property Sheet reflects averages derived from product sample testing on limited production runs, and may be changed without notice. Actual product properties are subject to normal manufacturing and testing tolerances. This is especially true for conventional measurements of *weight, thickness, and density*. This Typical Property Sheet is not intended to represent, replace, or be used as a proxy for a specific product sales specification. Please refer to our website at www.floormuffler.com for the most up to date product information, data, and installation instructions.

Let's get social



floormuffler.com
 1800 440 6008

