

FLOOR MUFFLER® LVT ENCORE

FloorMuffler® LVT encore is a high performance Acoustic Underlayment & Moisture Barrier for use in residential and commercial flooring applications.

PRODUCT SPECS

SPECS	STANDARD SIZE	CONTRACTOR SIZE
Coverage area	100 sf	600 sf
Width	39 in	72 in
Length	30.75 ft	100 ft
Diameter	5.5 in	8.5 in
Weight	2 lb	13 lb
Rolls/Carton	20	15
Carton/Skid	10	2

USES

Luxury Vinyl and Rigid Core flooring with pre-attached pad

METHODS

Floating Installations.

APPLICATIONS



Residential




Commercial

MATERIAL

Cross Linked, Closed Cell Polypropylene Foam (XLPP)


THICKNESS

1.1 mm




ACOUSTIC PERFORMANCE

69 IIC
62 STC
22 ΔIIC




MOISTURE PROTECTION

MVTR:
0.2 LBS
 1000FT² - 24HRS.



THERMAL PERFORMANCE

R Value per inch:
4.1 FT²-F-HR/
 BTU




COMPRESSIVE STRENGTH @25%

≥ 40 psi



FLAMMABILITY

CLASS A



ENVIROMENTAL

Mold & Mildew resistant:
YES
 VOCs:
Compliant with CA 01350

The data represented on this Typical Property Sheet reflects averages derived from product sample testing on limited production runs, and may be changed without notice. Actual product properties are subject to normal manufacturing and testing tolerances. This is especially true for conventional measurements of *weight, thickness, and density*. This Typical Property Sheet is not intended to represent, replace, or be used as a proxy for a specific product sales specification. Please refer to our website at www.floormuffler.com for the most up to date product information, data, and installation instructions.

Let's get social



floormuffler.com
 1 800 440 6008

