



FLOOR MUFFLER® FLEX

FloorMuffler® Flex is a high performance **Acoustic Underlayment** for use in residential and commercial flooring applications.

PRODUCT SPECS

SPECS	FLEX 2.0	FLEX 5.0	FLEX 10.0
Coverage area	200 sf	120 sf	60 sf
Width	48 in	48 in	48 in
Length	50 ft	30 ft	15 ft
Diameter	7.5 in	9.5 in	9.5 in
Weight	75	100	100
Rolls/Skid	20	25	20

USES

Laminate, Engineered, Solid Hardwood, Luxury Vinyl and Tile installations

METHODS

Floating, Nail down, and Double glue down installations.

APPLICATIONS



Residential




Commercial

MATERIAL

96% Recycled Rubber


THICKNESS

FLEX 2.0 FLEX 5.0 FLEX 10.0
2 mm 5 mm 10 mm



ACOUSTIC PERFORMANCE

FLEX 2.0	FLEX 5.0	FLEX 10.0
72 IIC	67 IIC	53 IIC
72 STC	62 STC	51 STC
78 HIIC	69 HIIC	61 HIIC



COMPRESSION SET B, 25%

MVTR:
40% MAX



TEAR STRENGTH

Value:
30 PPI, MIN



TENSILE STRENGTH

Value:
80 PSI, MIN



ENVIROMENTAL

VOCs:
Washington State
IAQ Compliant
LEED Points
up to 9 points

The data represented on this Typical Property Sheet reflects averages derived from product sample testing on limited production runs, and may be changed without notice. Actual product properties are subject to normal manufacturing and testing tolerances. This is especially true for conventional measurements of *weight, thickness, and density*. This Typical Property Sheet is not intended to represent, replace, or be used as a proxy for a specific product sales specification. Please refer to our website at www.floormuffler.com for the most up to date product information, data, and installation instructions.

Let's get social



floormuffler.com
1 800 440 6008

