



## FLOORMUFFLER® LVT ULTRASEAL

floorMuffler® LVT is a high performance Acoustic Underlayment & Moisture Barrier for use in residential and commercial flooring applications.

### PRODUCT SPECS

SPECS	STANDARD SIZE	CONTRACTOR SIZE
Coverage area	100 sf	600 sf
Width	35 in	72 in
Length	34.3 ft	100 ft
Diameter	5.75 in	8.5 in
Weight	2 lb	13 lb
Rolls/Carton	15	15
Carton/Skid	10	2

### USES

Luxury Vinyl Tile and Plank flooring installations

### METHODS

Floating and Double glue down installations.

### APPLICATIONS



Residential




Commercial

### MATERIAL

Cross Linked, Closed Cell Polypropylene Foam (XLPP)


### THICKNESS

1 mm



## ACOUSTIC PERFORMANCE

**71** IIC  
**66** STC  
**25** ΔIIC



## MOISTURE PROTECTION

MVTR:

**0.2** LBS  
1000FT<sup>2</sup> - 24HRS.



## THERMAL PERFORMANCE

R-Value per inch:

**4.1** FT<sup>2</sup>-F-HR/  
BTU



## COMPRESSIVE STRENGTH @25%

**≥ 40** psi



## FLAMMABILITY

**CLASS A**



## ENVIRONMENTAL

Mold & Mildew resistant:

**YES**

VOCs:

**Compliant with  
CA 01350**

The data represented on this Typical Property Sheet reflects averages derived from product sample testing on limited production runs, and may be changed without notice. Actual product properties are subject to normal manufacturing and testing tolerances. This is especially true for conventional measurements of *weight, thickness, and density*. This Typical Property Sheet is not intended to represent, replace, or be used as a proxy for a specific product sales specification. Please refer to our website at [www.floormuffler.com](http://www.floormuffler.com) for the most up to date product information, data, and installation instructions.

Let's get social



[floormuffler.com](http://floormuffler.com)

1 800 440 6008

