

FLOOR MUFFLER® LVT ULTRASEAL

FloorMuffler® LVT is a high performance Acoustic Underlayment & Moisture Barrier for use in residential and commercial flooring applications.

PRODUCT SPECS

SPECS	STANDARD SIZE	CONTRACTOR SIZE
Coverage area	100 sf	600 sf
Width	35 in	72 in
Length	34.3 ft	100 ft
Diameter	5.75 in	8.5 in
Weight	2 lb	13 lb
Rolls/Carton	15	15
Carton/Skid	10	2

USES

Luxury Vinyl Tile and Plank flooring installations

METHODS

Floating and Double glue down installations.

APPLICATIONS



Residential



Commercial

MATERIAL

Cross Linked, Closed Cell Polypropylene Foam (XLPP)


THICKNESS

1 mm



ACOUSTIC PERFORMANCE

71 IIC
66 STC
25 ΔIIC



MOISTURE PROTECTION

MVTR:

0.2 LBS
1000FT² - 24HRS.



THERMAL PERFORMANCE

R Value per inch:

4.1 FT²-F-HR/
BTU



COMPRESSIVE STRENGTH @25%

≥ 40 psi



FLAMMABILITY

CLASS A



ENVIROMENTAL

Mold & Mildew resistant:

YES

VOCs:

**Compliant with
CA 01350**

The data represented on this Typical Property Sheet reflects averages derived from product sample testing on limited production runs, and may be changed without notice. Actual product properties are subject to normal manufacturing and testing tolerances. This is especially true for conventional measurements of *weight, thickness, and density*. This Typical Property Sheet is not intended to represent, replace, or be used as a proxy for a specific product sales specification. Please refer to our website at www.floormuffler.com for the most up to date product information, data, and installation instructions.

Let's get social



floormuffler.com
1800 440 6008

