

floorMuffler® FLEX

it's what's underneath that counts®



FloorMuffler® Flex is a high performance Acoustic Rubber Underlayment for use in residential and commercial flooring applications. As part of our *Premium* Collection, FloorMuffler Flex is the ideal choice for most Tile, Laminate, Engineered and Solid hardwood flooring installations. FloorMuffler Flex can be used in Floating, Nail down, and Double glue down installations.

TYPICAL PHYSICAL PROPERTIES SHEET



floorMuffler® FLEX

High Performance Acoustic Rubber Underlayment

it's what's underneath that counts®



FloorMuffler® Flex is a high performance Acoustic Rubber Underlayment for use in residential and commercial flooring applications. As part of our *Premium* Collection, FloorMuffler Flex is the ideal choice for most Tile, Laminate, Engineered and Solid hardwood flooring installations. FloorMuffler Flex can be used in Floating, Nail down, and Double glue down installations.

TYPICAL PHYSICAL PROPERTIES SHEET

GENERAL PROPERTIES	FloorMuffler® Flex 2.0	FloorMuffler® Flex 5.0	FloorMuffler® Flex 10.0
Construction	92% Recycled Rubber	92% Recycled Rubber	92% Recycled Rubber
Thickness	2 mm	5 mm	10 mm
Coverage	200 sf	120 sf	60 sf
Standard Roll Size	48" wide x 50 lf	48" wide x 30 lf	48" wide x 15 lf
ProductGade	Premium	Premium	Premium

PERFORMANCE

Impact Isolation Class (IIC)*	72 db	67 db	53 db
High-Frequency Impact Isolation Class (HIIC)*	78 db	69 db	61 db
Sound Trasmission Class*	72 db	62 db	51 db
Mold and Mildew Resistant	Yes	Yes	Yes
Volatile Organic Compounds (VOCs)	Surpasses California Section 01350	Surpasses California Section 01350	Surpasses California Section 01350
Recylcable	Yes	Yes	Yes
Contributes to Earning LEED Points	Yes, 9 points	Yes, 9 points	Yes, 9 points

PACKAGING

Rolls / Skid	25	25	20
Skids / TL	20	20	20
Rolls / TL	500	500	400
SF / Skid	5,000	3,000	1,200
SF / TL	100,000	60,000	24,000

* FloorMuffler Flex 2.0 and FloorMuffler Flex 5.0 were tested with wood flooring and 8" concrete slab with gypsum board suspended ceiling. FloorMuffler Flex 10.0 was tested with wood flooring and 6" concrete slab without a drop ceiling.

The data represented on this Typical Property Sheet reflects averages derived from product sample testing on limited production runs, and may be changed without notice. Actual product properties are subject to normal manufacturing and testing tolerances. This is especially true for conventional measurements of weight, thickness, and density. This Typical Property Sheet is not intended to represent, replace, or be used as a proxy for a specific product sales specification. Please refer to our website at www.floormuffler.com for the most up to date product information, data, and installation instructions.



CERTIFIED BY
SCS Global Services

Let's Get Social



www.floormuffler.com • 1-800-440-6008

Diversified Industries • 121 High Hill Road • Swedesboro, NJ 08085

Premium
GRADE