



## FLOORMAT FANFOLD

FloorMat™ FanFold is an Acoustic Underlay-ment & Moisture Barrier for use in residential and commercial flooring applications. Available with self-sealing lip & tape system.

### USES

Laminate, Engineered and Solid hardwood flooring installations.

### METHODS

Floating Installations.

### APPLICATIONS



Residential



Commercial

### MATERIAL


XPS Foam + ALU Film

### THICKNESS

2 mm


### PRODUCT SPECS

SPECS	STANDARD SIZE
Coverage area	100 sf
Width	46.69 in
Length	25.94 ft
Weight	3 lb
Units /Carton	1
Cartons/Skid	112



## ACOUSTIC PERFORMANCE


**72** IIC  
**67** STC



## MOISTURE PROTECTION

MVTR:


**.5** LBS  
1000FT<sup>2</sup> - 24HRS.



## THERMAL PERFORMANCE

R Value per inch:

**5** FT<sup>2</sup>-F-HR/  
BTU



## COMPRESSIVE STRENGTH @25%

**≥ 8.5** psi



## ENVIROMENTAL

Mold & Mildew resistant:

**YES**

VOCs:

**Compliant with  
CA 01350**

The data represented on this Typical Property Sheet reflects averages derived from product sample testing on limited production runs, and may be changed without notice. Actual product properties are subject to normal manufacturing and testing tolerances. This is especially true for conventional measurements of *weight, thickness, and density*. This Typical Property Sheet is not intended to represent, replace, or be used as a proxy for a specific product sales specification. Please refer to our website at [www.floormuffler.com](http://www.floormuffler.com) for the most up to date product information, data, and installation instructions.

Let's get social



[floormuffler.com](http://floormuffler.com)  
1 800 440 6008

