



FLOORMAT™ FANFOLD

FloorMat™ FanFold is an Acoustic Underlay-ment & Moisture Barrier for use in residential and commercial flooring applications. Available with self-sealing lip & tape system.

USES

Laminate, Engineered and Solid hardwood flooring installations.

METHODS

Floating Installations.

APPLICATIONS



Residential



Commercial

MATERIAL


XPS Foam + ALU Film

THICKNESS

2 mm


PRODUCT SPECS

SPECS	STANDARD SIZE
Coverage area	100 sf
Width	46.69 in
Length	25.94 ft
Weight	3 lb
Units /Carton	1
Cartons/Skid	112



ACOUSTIC PERFORMANCE

72 IIC
67 STC



MOISTURE PROTECTION

MVTR:

.5 LBS
1000FT² - 24HRS.



THERMAL PERFORMANCE

R-Value per inch:

5 FT²-F-HR/
BTU



COMPRESSIVE STRENGTH @25%

≥ 8.5 psi



ENVIRONMENTAL

Mold & Mildew resistant:

YES

VOCs:

**Compliant with
CA 01350**

The data represented on this **Typical Property Sheet** reflects averages derived from product sample testing on limited production runs, and may be changed without notice. Actual product properties are subject to normal manufacturing and testing tolerances. This is especially true for conventional measurements of *weight, thickness, and density*. This **Typical Property Sheet** is not intended to represent, replace, or be used as a proxy for a specific product sales specification. Please refer to our website at www.floormuffler.com for the most up to date product information, data, and installation instructions.

Let's get social



floormuffler.com

1 800 440 6008

