



FLOOR MUFFLER® FLEXLOCK

FloorMuffler® FlexLock is a Premium Grade highly engineered recycled vulcanized rubber floor.

PRODUCT SPECS

SPECS	STANDARD SIZE
Coverage area	3.67 sf
Width	23 in
Length	23 in
Weight	6 lb
Units/Skid	340

USES

Rubber floor or fitness rooms, gyms, garages, and more

METHODS

Floating Installations.

APPLICATIONS



MATERIAL

Recycled Vulcanized Rubber



ACOUSTIC PERFORMANCE

51 IIC
22 ΔIIC



STATIC LOAD LIMIT

0.020
(@1000psi)
as per ASTM D2859



FLAMMABILITY

PASS Pill test as
per ASTM D2859



ENVIROMENTAL

VOCs:
Washington State
IAQ Compliant
LEED Points
up to 9 points

The data represented on this [Typical Property Sheet](#) reflects averages derived from product sample testing on limited production runs, and may be changed without notice. Actual product properties are subject to normal manufacturing and testing tolerances. This is especially true for conventional measurements of *weight, thickness, and density*. This [Typical Property Sheet](#) is not intended to represent, replace, or be used as a proxy for a specific product sales specification. Please refer to our website at www.floormuffler.com for the most up to date product information, data, and installation instructions.

Let's get social



floormuffler.com
1 800 440 6008

